

tesa® 60021

Spray glue PERMANENT, 500ml

PRODUCT INFORMATION

Product Description

tesa® Spray Glue PERMANENT 60021 is a very versatile glue for permanently bonding materials such as paper, card-board, felt, fabric, film, wood, leather, polystyrene and many different plastics.

- For clean, cost efficient, secure and fast bonding of large areas
- Suitable for light to medium-weight material with smooth to uneven surfaces
- The glue is dispersed finely and evenly
- Fast-drying and resistant against damp and mechanical and thermal stresses
- Suitable for gluing Styrofoam
- Free from silicone

Main Application

tesa® Spray Glue PERMANENT 60021 is outstandingly suitable for general industrial applications like

- Pattern making
- Marking of palettes
- Attaching wiring diagrams and labels
- Mounting of P.O.S-Displays
- Permanent mounting of posters and templates e.g. on Styrofoam
- Bonding of thin decorative film, foil and fabric

and many other professional applications in industry and craft. Furthermore, tesa® Spray Glue PERMANENT 60021 is suitable for the general use at home.

Technical Data

■ Colour	pale cream	■ Solvent based on	dearomatized special petrol and acetone
■ Temperature resistance from	-20 °C	■ Propellant based on	propane/butane
■ Temperature resistance up to	60 °C	■ Recommended distance of spraying	30 cm
■ Glue based on	synthetic rubber	■ Recommended time before bonding	1-5 min

Properties

■ Permanent bonding result	++	■ Temporary bonding result	-
----------------------------	----	----------------------------	---

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

For latest information on this product please visit <http://l.tesa.com/?ip=60021>

Page 1 of 2 / As of 07/04/14

tesa SE

Quickbornstraße 24
20253 Hamburg
Germany
Phone: +49 (40) 4909 101

tesa SE
A Beiersdorf Company

<http://www.tesa.com>

tesa tape inc.

5825 Carnegie Boulevard
Charlotte, N.C. 28209
United States of America
Phone: +1 (704) 554 0707
Fax: +1 (704) 553 5634
<http://www.tesatape.com>

tesa tape Asia Pacific Pte. Ltd.

9 North Buona Vista Drive
#04-01 The Metropolis
Tower 1
Singapore 138588
Tel: +65 6697 9888
Fax: +65 6659 6390
<http://www.tesa-asia.com>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.

Additional Info

- tesa offers two complementary Spray Glues: 60022 EXTRA STRONG and 60023 REPOSITIONABLE
- Observe the safety-information on the spray-can
- Shake can well before use and remove any dried-on glue from the nozzle
- For new applications, test suitability by gluing a sample
- The parts to be bonded must be dry and free from dust and grease. We recommend cleaning with tesa® INDUSTRY CLEANER 60040
- After use, turn can upside-down and expel glue from nozzle until only propellant comes out
- Overspray from Spray Glues can easily be removed with tesa® 60042 ADHESIVE REMOVER
- Refer to special instructions/safety data sheets: www.tesa.com/safety

For latest information on this product please visit <http://l.tesa.com/?ip=60021>

Page 2 of 2 / As of 07/04/14

tesa SE

Quickbornstraße 24
20253 Hamburg
Germany
Phone: +49 (40) 4909 101

tesa SE
A Beiersdorf Company

<http://www.tesa.com>

tesa tape inc.

5825 Carnegie Boulevard
Charlotte, N.C. 28209
United States of America
Phone: +1 (704) 554 0707
Fax: +1 (704) 553 5634
<http://www.tesatape.com>

tesa tape Asia Pacific Pte. Ltd.

9 North Buona Vista Drive
#04-01 The Metropolis
Tower 1
Singapore 138588
Tel: +65 6697 9888
Fax: +65 6659 6390
<http://www.tesa-asia.com>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.