

## tesa® 4671

### Acrylic coated cloured duct tape

tesa® 4671 is a strong acrylic paste coated cloth tape. It is based on a 120 mesh woven rayon fabric backing and a natural rubber adhesive.

tesa® 4671 is a strong cloth tape for almost every application.

#### Features:

- high adhesion even on rough surfaces
- excellent tensile strength
- easy to write on
- conformable
- easy to remove without residues
- no unpleasant odour
- less reflective surface
- available in 6 colours: black, white, grey, red, blue, and green

### Main Application

- Indoor and outdoor applications
- Bundling and reinforcing of heavy pipes
- Suitable for several applications in the event sector
- Fixing of carpets during exhibitions
- Floor marking
- Covering sharp edges

### Technical Data

▪ Backing material	acrylic-coated cloth	▪ Elongation at break	9 %
▪ Total thickness	280 µm	▪ Tensile strength	70 N/cm
▪ Type of adhesive	natural rubber	▪ Temperature resistance (30 min)	140 °C
▪ Adhesion to steel	3.5 N/cm	▪ Mesh	120 count per square inch

### Properties

▪ Hand tearability	●●●●	▪ Suitable for die cutting	yes
▪ Straight tear edges	●●●●	▪ Abrasion resistance	●●●●
▪ Easy to write on	yes	▪ Water resistance	●●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

### Additional Information

Recommendation: please conduct a test on the application surface before using the product.

For latest information on this product please visit <http://l.tesa.com/?ip=04671>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.