

**tesa 51570**

**Double Sided Non-Woven Tape**

**Product Description/  
Application:**

tesa 51570 is a double sided tape with a non-woven backing. It is used for permanent mounting of metal and plastic materials, e.g. aluminium, polystyrene, polypropylene, ABS. The thick layer of adhesive bonds well on uneven surfaces and has a very high initial bond.

It is not recommended to use tesa 51570 where a temperature load of over 60° C prevails for a long period.

**Dimensions:**

Length:	50 m
Widths:	50mm, 1350 mm
other widths:	upon request

**Technical Data:  
(mean values)**

Backing	Adhesion / Steel	Adhesion/ Polystyrene	Adhesive	Thickness	Tensile Strength
Non Woven	12 N/ 10 mm	8 N/10 mm	Synthetic rubber	0,130 mm (without liner)	9 N/10 mm

7100 10/2003

tesa AG  
Quickbornstraße 24  
D-20253 Hamburg  
Telephone +49-40-49 09 6023  
Telefax +49-40-49 09 4621

tesa self-adhesive tapes are used successfully in many sectors to solve a variety of problems. Our publications contain numerous examples of such uses, intended to help towards a solution of your particular problems. Each tesa product has been developed for a particular range of applications. Nevertheless, experience has shown that even for one and the same objective, the exact requirements may differ from case to case. We, therefore, recommend that you carry out your own tests in each case, to confirm that the tesa self-adhesive tape which you envisage using is appropriate for your particular application. The Advisory Section of our Technical Service Department will be happy to assist. All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty.